

Specification Sheet

Part Number: TSR3W-29-1


Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.

PVC construction is lightweight, durable and more affordable than metallic raceway systems.

Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing.

Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.

Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.



External Corner Cover, 1-3/4", 1" Bend Radius, PVC, White, Bag of 10

Article Number 250-32905

Type TSR3-29-1

Color White (WH)

Quantity Per pack

Product Description	HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. TSR surface raceway systems can be used to route a variety of communication cable, including high speed UTP and fiber optic cable.
Short Description	External Corner Cover, 1-3/4", 1" Bend Radius, PVC, White, Bag of 10
Global Part Name	TSR3-29-1-PVC-WH
Length L (Imperial)	5.320
Length L (Metric)	135.13
Width W (Imperial)	1.983
Width W (Metric)	50.34
Height H (Imperial)	5.320
Height H (Metric)	135.13
Wall Thickness WT (Imperial)	0.080
Wall Thickness WT (Metric)	2.03

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability UL 94 V-0

Halogen Free No

UV Resistant (Yes/No) No

Use Conditions For Indoor Use Only

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 10

Package Quantity (Metric) 10

Customs Number 3925900000

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)